

BOTTOM LINE ASSORTMENT**R 272 C***control*

Type heater	Control
Brand name	Stover
Model no.	R 272 C (Type C)
Toyotomi Model Name	RS-L27D-SV
Brown	8713508710402



Control

TECHNICAL SPECIFICATIONS

Burner type	Single Combustion (BL)	Dimensions (mm)	Width	428
Capacity (W) max.	2900	(including base plate)	Depth	295
Tank capacity	4.0 litres		Height	455
Burning time tank (hr)	13 hours	Fuel consumption (l/hr)	Max	0.302
Suitable space (m²)	32-42	Fuel consumption (g/hr)	Max	242
Suitable space (m³)	80-105	Wick height (mm)		9 to 11
Weight heater (kg)	7.5	Internal diameter (mm)		65
Languages manual	French	Material wick		FELT
Accessories	Transportation cap, A5 size operating manual			
Guarantee	2 years (except ignition coil, glass cylinder(s) and wick)			



THE 10 MOST IMPORTANT SPARE PARTS

Spare part description	Model	EAN Code
① Glass fibre felt wick	F	8713508001517
② Removable fuel tank	D	8713508401607
③ Fuel tank cap high	A	8713508400600
④ Fuel filter open	C	8713508702186
⑤ Ignition coil		8713508400402
⑥ Wick sleeve		8713508001616
⑦ Glass cylinder		8713508020808
⑧ Transportation cap U38		8713508402505
⑨ Manual fuel pump		8713508400105
⑩ Tank lid		8713508000510




Transportation Cap

Strictly for internal use




Gross Weight:



Automatic Tip-Over Switch



Open Filter



Room Temperature Thermistor



Extinguishing stop

FEATURES STOVER R 272 C

- Automatic Tip-Over-Switch: The heater is shut off in case of knocking over the heater.
- High Efficiency: the heater has a 99.99% heat efficiency with infrared-ray heating.
- Great Heating Capacity: The 2.9 kW capacity ensures a capacity to heat an entire room.
- No Installation: This heater needs no wires, no pipes and no flues. This makes the heater very mobile.
- Extinguishing Stop: This heater is equipped with an extinguishing stop. By one simple push on the stop, the heater will be turned off.
- Room Temperature Thermistor: This heater automatically shuts off when used in a room with too high a room temperature (oxygen shortage).
- Made in Japan: Complies with International Quality Control Standard ISO 9000.
- Superior quality and finish of top-plate and cabinet.
- Wick-Stop: The wick-stop mechanism prevents the consumer to adjust the burner and therefore limits the exhaust of CO to stay below 50 ppm.

Remarks

- Equipped with a wick-stop mechanism according to NF regulations
- No fuel indicator
- Grill conform NF regulations
- Equipped with a white and cheaper felt wick. This wick will not be ordered as a spare part because it is interchangeable with the existing felt wick for this heater
- No batteries included
- No manual fuel pump included
- No plastic bag
- No plumb bob
- **New:**
 - automatic burner switch off 5 sec. after fuel tank removal.
 - top plate of the battery compartment will be fastened with a small screw.
 - top and bottom end of the carton box will be brown instead of white.

*Patent Toyotomi



Strictly for internal use